


E1W Double Compression Cable Gland



MM-1W25L 2N B2 (3/4"NPT)



Double Compression Cable Gland For Armoured Cables

CABLE GLAND SIZE DETAILS

Type	E1W Double Compression Cable Gland
Cable Types	Armoured (Steel wire armour (SWA) Aluminium wire armour (AWA)
Application	For use with all types of SWA cable for Indoor and outdoor application. Used in applications where it is essential to provide an IP66 seal on the outer sheath. Armour lock with separate armour locking ring, ideal for checking electrical continuity
Standard	BS6121: Part 1: 2005. EN50262
Option thread	NPT
Gland Material	Brass (CuZn39PB3)
IP Rating	IP66

CODE	MM-1W25L 2N B2 (3/4"NPT)
CABLE GLAND SIZE	25L
NPT	3/4"
Thread Length "E"	10
Cable Diameter "A"	
MIN	16.50
MAX	20

Sealing Method	Double Compression Sealing (Sealing on both Outer and Inner Sheath)	Cable Diameter "B"	
Operating Temperature	Standard Seals (Nitrile): -20°C TO 80°C. On Request (Silicone): -50°C To +160°C	MIN	21.50
Finish	Natural Brass or Nickel Plated or Electroless Nickel Plated	MAX	27.00
Accessories	PVC Shroud, SLSF Shroud, Lock Nut, Earth Tag, Serrated Washer, Adaptor / Reducer.	Across Flat	36
		Across Corner	39.50

-
- * Degrees of protection (IP Code) : IP66 / IP68 (1.5 meter, 2 Hours)
 - * All the dimensions given are in Millimeters (mm)
 - * Can be also provided in Kit Packing as per requirement