


# E1W Double Compression Cable Gland



## MM-E1W90L B2 (M90)



### Double Compression Cable Gland For Armoured Cables

### CABLE GLAND SIZE DETAILS

**Type** E1W Double Compression Cable Gland

**CODE** MM-E1W90L B2 (M90)

**Cable Types** Armoured (Steel wire armour (SWA) Aluminium wire armour (AWA))

**CABLE GLAND SIZE** 90L

**Application** For use with all types of SWA cable for Indoor and outdoor application. Used in applications where it is essential to provide an IP66 seal on the outer sheath. Armour lock with separate armour locking ring, ideal for checking electrical continuity

**Metric** M90x1.5

**Thread Length "E"** 20

**Standard** BS6121: Part 1: 2005. EN50262

**Cable Diameter "A"**

**Option thread** Metric

**MIN** 67

**Gland Material** Brass (CuZn39PB3)

**MAX** 78.50

|                              |                                                                                                       |                           |        |
|------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------|--------|
| <b>IP Rating</b>             | IP66                                                                                                  |                           |        |
| <b>Sealing Method</b>        | Double Compression Sealing<br>(Sealing on both Outer and Inner Sheath)                                | <b>Cable Diameter "B"</b> |        |
| <b>Operating Temperature</b> | Standard Seals (Nitrile): -20°C TO 80°C.                                                              | <b>MIN</b>                | 78.50  |
| <b>Finish</b>                | On Request (Silicone): -50°C To +160°C<br>Natural Brass or Nickel Plated or Electroless Nickel Plated | <b>MAX</b>                | 91     |
| <b>Accessories</b>           | PVC Shroud, SLSF Shroud, Lock Nut, Earth Tag, Serrated Washer, Adaptor / Reducer.                     | <b>Across Flat</b>        | 104    |
|                              |                                                                                                       | <b>Across Corner</b>      | 114.50 |

---

\* Degrees of protection (IP Code) : IP66 / IP68 (1.5 meter, 2 Hours)

\* All the dimensions given are in Millimeters (mm)

\* Can be also provided in Kit Packing as per requirement