



IP 68 PG Threaded

Single Compression Cable Gland

MM-PG29-20 X6 (PG29)



CABLE GLAND SIZE DETAILS

Type	IP 68 PG Threaded Single Compression Cable Gland
Cable Types	Unarmoured
Option thread	PG
Gland Material	Stainless Steel (SS316L)
IP Rating	IP68

Operating Temperature Standard Seals: -20°C to +90°C

Finish	Nickel Plated
Accessories	Matching Accessories available like PVS Shrouds, Lock Nuts & "O" Ring as per requirement

CODE MM-PG29-20 X6 (PG29)

CABLE SIZE METRIC PG29

THREAD SIZE "B"
METRIC PG29

THREAD LENGTH "C"
SHORT 8
LONG 12

MATERIAL GRADE CONFIGURATIONS	
UL94V0	PVC Insert : Nylon 66 Rubber seal : Neoprene (FR) O Ring : Neoprene (FR)
High Temperature	PVC Insert : PVDF Rubber seal : Viton O Ring : Viton
Regular Application	PVC Insert : Nylon 6 Rubber seal : EPDM O Ring : NBR

ACROSS FLAT 40

CABLE RANGE "A"
MIN 13
MAX 20

-
- * Degrees of protection (IP Code) : IP66 / IP68 (1.5 meter, 2 Hours)
 - * All the dimensions given are in Millimeters (mm)
 - * Can be also provided in Kit Packing as per requirement